

|  |   |   |
|--|---|---|
| Wideband RF Power Amplifier<br><b>CRF-PA-6000M18000M-50W</b> | Frequency Range<br>6,000 – 18,000 MHz<br><br>Rated Output Power<br>50 W | Connector<br>Input: SMA-Female<br>Output: N-Female<br><br>Package Size<br>330 × 200 × 60 mm |
|--|---|---|

## Electrical Characteristics

Test conditions: 50Ω system, unless otherwise specified.

| Parameter             | Min | Typ  | Max   | Units   |
|-----------------------|-----|--|-------|---------|
| Frequency Range       |     | 6,000 – 18,000 MHz   |       |         |
| Gain                  | 50  |  |       | dB      |
| Gain Flatness         | -4  |  | 4     | dB      |
| Input VSWR            |     |  | 2 : 1 |         |
| Input power           |     |  | 0     | dBm     |
| Rated Output Power    | 50  |  |       | W       |
| Power Supply          |     | DC 28V   |       |         |
| Harmonics             |     |  | -10   | dBc     |
| Spurious              |     |  | -60   | dBc     |
| RF Connectors In/Out  |     | Input: SMA-Female<br>Output: N-Female  |       |         |
| Control Interface     |     | RS485  |       |         |
| Dimensions            |     | 330 × 200 × 60   |       | mm      |
| Impedance             |     | 50   |       | Ω       |
| Operating Temperature | 0   |  | 50    | °C      |
| Storage Temperature   | -20 |  | 75    | °C      |
| Cooling Method        |     | Air cooling  |       |         |
| Noise Floor           |     |  | -40   | dBm/MHz |
| Application           |     | Test & measurement /<br>communication /<br>interference / aviation<br>control                                  |       |         |
| Built-in protection   |     | over-voltage, over-<br>temperature, over-<br>drive and VSWR.<br>Design based on<br>advanced GaN<br>technology. |       |         |

## DC Connector & Pin Definitions

| Interface / Pin     | Description            | Specification / Level   |
|---------------------|------------------------|---|
| Ground Terminal     | Ground                 | Ground Return   |
| 2W2 Connector Pin 1 | Power Supply (VCC)     | +24V to 32V DC (Nominal: +28V)  |
| 2W2 Connector Pin 2 | Power Ground           | GND   |
| DB9 Pin 1           | Serial Communication   | RS485 (-)   |
| DB9 Pin 2           | Serial Communication   | RS485 (+)   |
| DB9 Pin 3           | PTT (PA Control)       | PA ON: 3.3V PA OFF: 0V  |
| DB9 Pin 4           | Attenuation Adjustment | Input range: 0 - 3.0V (DC) 0.5V = Min Attenuation<br>3.0V = Max Attenuation |
| DB9 Pin 5           | Input Monitor          | Input detection voltage output  |
| DB9 Pin 6           | Forward Power Monitor  | Forward detection voltage output  |
| DB9 Pin 7           | Reverse Power Monitor  | Reverse detection voltage output  |
| DB9 Pin 8           | Temperature Monitor    | Temperature detection voltage output  |
| DB9 Pin 9           | Ground                 | GND   |

|   |  |  |
|---|--|--|
| <b>Model</b><br>CRF-PA-6000M18000M-50W  | <b>Package Size</b><br>330 × 200 × 60 mm                         | <b>Gain</b><br>50dB  |
| <b>Connector Reference</b><br>RF IN: SMA-Female<br>RF OUT: N-Female<br>Control: RS485 | <b>Power / Cooling</b><br>Supply: 28 VDC<br>Cooling: Air cooling | <b>Release Note</b><br>Mechanical drawing is provided for installation reference. Final dimensions are subject to the production unit. |

|   |   |
|---|---|
| <b>Applications</b><br>Test & measurement / communication / interference / aviation control | <b>Customization</b><br>Optional built-in coupler is available. |
|---|---|

### Compliance / Quality Framework

|                |          |          |           |
|----------------|----------|----------|-----------|
| RoHS Compliant | CE / FCC | ISO 9001 | GJB 9001C |
|----------------|----------|----------|-----------|

Test data and pattern files can be supplied for project review where applicable.